



TLINFOVISION



LED Information Kiosk/Wall Display Systems

Trans-Lux TL InfoVision LED Information Kiosk/Wall Display Systems combines TL InfoVision LED Information Displays and a back-lit advertising panel into an integrated freestanding kiosk or wall display. The main display can receive a live data feed, or can be programmed to cycle up to twenty pages of information. A single line information display can scroll messages or display time and date.

TRANSLUX



TLINFOVISION

LED Information Kiosk/Wall Display Systems

Trans-Lux delivers high-impact messaging via easy to use kiosk or wall displays. The back-lit ad panel is custom printed utilizing your supplied artwork. Multiple displays can be networked and easily updated via PC. It's the perfect solution for posting patient names while waiting for pharmacy prescriptions to be filled or as a silent salesperson at an auto dealership or financial institution. Other applications include:

- » Airports
- » Banks and credit unions
- » Healthcare facilities and pharmacies
- » Hotels
- » Lobbies
- » Lounges and waiting areas
- » Retail stores

Display Specifications

Main display

LED color standard	green / custom colors available
Size	8 lines
Enclosure painted aluminum	bronze tone or customizable
Fascia matte finish	Lexan
Input devices	keyboard, PC or laptop computer
Network capability	up to 30 direct, unlimited by modem or Ethernet

Message line display

LED color	red
Memory	30,000 characters
Display Modes	12
Memory back-up	30 days
Construction	100% solid state electronics
Power supply	120VAC or 240VAC @ 50 Hz / 60 Hz
Current requirements	2.3A @ 120V, 1.3A @ 240V
Standard interfaces	RS422 (preferred) or RS232, Ethernet TCP / IP
Transmission speed	Serial - 300 to 9,600 baud, 10 Base-T
Modems	Bell 103A standard
Mounting (wall mount unit only)	standard wall mount bracket included
Limited warranty	1 year

Software

- » Trans-Lux Software (standard)
- » Trans-Lux Patient Notification Software (optional)

Minimum Hardware Configuration

IBM PC or compatible running Windows XP or later:

- » 640K RAM
- » 10 MB hard disk drive
- » One serial port for direct connect
- » RS232 to RS422 converter
- » VGA compatible display adapter

All specifications are approximate and subject to change without notice.

TRANSLUX

Trans-Lux Corporation
 26 Pearl Street, Norwalk, CT 06850
 888.485.9669 • www.Trans-Lux.com